

Put on the rest of the undergarment. Don the suit as far as the thighs and attach the silicone hose to the attachment nut socket. Complete donning the suit.

Using

Push the lid down and turn to close (off) and turn top open (on). When using, turn the valve open and then urinate.

Note! The valve should be open in water - expanding air is relieved through the valve. Do not wait too long before relieving yourself. Urinating often is better. To minimize the pressure difference, maintain a horizontal position while urinating.

Doffing

Turn the Pee Valve open. Open the suit and undergarment. Squeeze as much urine as possible out of the hose, from the uridome and outwards, through the valve.

Disconnect the hose from the attachment nut socket. If possible, cover the socket to avoid further spill/leakage. After doffing the suit; remove the dump valve, rinse it and insert the blanking plug (if available).

Use the disassembly tool to clean the valve. Turn counter clockwise to disassemble the top lid from valve body.

Wash the entire valve with luke warm soapy water and rinse thoroughly with warm water.

Store the valve open (turned off) and disconnected from the hose. Uridomes are preferably used once only.



Document produced by
 Johanna Strömgren
 2012-03-12

Pee Valve

11920/11925

- 11920 Pee Valve set with Tool and Valve Port (A, B and C)
- 11925 Pee Valve complete set (A, B, C, D and E)



Parts list

A	Pee Valve	1 pcs
B	Disassembly Tool (item no. 18417B)	1 pcs
C	Valve Port (item no. 60895)	1 pcs
D	Blanking plug (item no. 60340)	1 pcs
E	Uridome 30 mm (item no. 11908)	2 pcs

Extra Uridomes

- 25 mm (item no. 11907)
- 30 mm (item no. 11908)
- 35 mm (item no. 11909)

On/Off valve for easy maneuver.

Twin Check Valves for safe evacuation and no outer leakage.

Valve Port to be glued to the suit.

Pressure compensated.

Easy to clean. Disassembly tool is included.



The SI TECH Pee Valve is intended for attachment in a Valve Port that is permanently glued to the suit. Recommendations on adhesive types, solvents and installation to the suit material must come from your suit manufacturer or an authorized suit repair facility. The Pee Valve is furnished with a pressure compensation checkvalve inside the internal nut.

Suit preparations

Attach the valve into the suit on the upper and inner part of the thigh (minimum 15 mm from the crotch), easily accessible when turning dump valve on and off. (A blanking plug (60340) is required when the Pee Valve is not in use.)



Attach the Pee Valve into the Valve Port with the socket of the attachment nut pointing upwards.

The undergarment also needs to be penetrated (i.e. on the thigh) to give way for the hose. To keep the parts on the inside of the suit as low as possible, the attachment nut is designed to be fitted against the Valve Port directly. No suit material can remain between the connecting nut and the Valve Port.

The hole in the fabric has to be bigger than usual (a minimum diameter is 55,5 mm). This method of connection must be used.

Otherwise, the connection between the valve and the attachment nut will be insufficient or impossible.

Assembly of hose and uridome

To ease the insertion, angle cut the silicone hose >45 degrees. Insert the chamfered end through the uridome extension.

To secure the hose from slipping out; apply silicone sealant or Aquasure on the last 30 mm of the hose. Pull the rest of the hose, until it does not protrude, into the cup of the uridome.

Adjust the length of the hose (still allowing you to stretch your legs when swimming). Cut the end perpendicular.

Donning

Relieve yourself before donning the suit. The uridome is put on the same way as a condom.

Make sure no hair is snagging in the self adhesive surface.

Put on the undergarment as far as the thighs and put the end of the hose through the hole.

Gently taping the hose to the body is a good idea. Make sure sharp bends and any potential squeeze of the hose are avoided.

